

Pathway to the Future

Control of Hazardous Energy Program (Lockout/Tagout)

Berryessa Union School District 1376 Piedmont Road, San Jose CA 95132 408-923-1800

Updated February 2018

Updated September 2020

Updated September 2021

The Control of Hazardous Energy (Lockout/Tagout) Program 1910.147

The following lockout/tagout program is provided to assist employees in complying with the requirements of 29 Code of Federal Regulations (CFR) 1910.147, as well as to provide other helpful information.

TABLE OF CONTENTS

Objective	Page 4
Assignment of Responsibility	Page 4
Procedures	Page 4-7
Attachment A- List of Authorized Personnel for Lockout Tagout Procedures	Page 8
Attachment B- Certification of Training	Page 9
Attachment C- Certification of Training (Affected Employee)	Page 10
Attachment D- Lockout/Tagout Inspection Form	Page 11
Attachment E- Outside Personnel/Contractor Certification	Page 12
Attachment F- Equipment Specific Procedure for BUSD	Page 13-16

OBJECTIVE

The objective of this procedure is to establish a means of positive control to prevent the accidental starting or activating of machinery or systems while they are being repaired, cleaned and/or serviced. This program serves to:

- A. Establish a safe and positive means of shutting down machinery, equipment and systems.
- B. Prohibit unauthorized personnel or remote control systems from starting machinery or equipment while it is being serviced.
- C. Provide a secondary control system (tagout) when it is impossible to positively lockout the machinery or equipment.
- D. Establish responsibility for implementing and controlling lockout/tagout procedures.
- E. Ensure that only approved locks, standardized tags and fastening devices provided by the company will be utilized in the lockout/tagout procedures.

ASSIGNMENT OF RESPONSIBILITY

- A. <u>Dan Norris</u>, Director of MOT, will be responsible for implementing the lockout/tagout program.
- B. <u>Dan Norris</u>, Director of MOT, is responsible for enforcing the program and insuring compliance with the procedures in the MOT departments.
- C. <u>Dan Norris</u>, Director of MOT, will conduct the annual inspection and certification of the authorized employees.
- D. <u>Authorized employees</u> are responsible for following established lockout/tagout procedures. An authorized employee is defined as a person who locks out or tags out machines or equipment in order to perform servicing or maintenance on that machine or equipment. An affected employee becomes an authorized employee when that employee's duties include performing servicing or maintenance covered under 1910.147, The Control of Hazardous Energy (lockout/tagout).
- E. <u>Affected employees</u> (all other employees in the facility) are responsible for insuring they do not attempt to restart or re-energize machines or equipment that are locked out or tagged out. An affected employee is defined as a person whose job requires him/her to operate or use a machine or equipment on which servicing or maintenance is being performed under lockout or tagout, or whose job requires him/her to work in an area in which such servicing or maintenance is being performed.

PROCEDURES

The ensuing items are to be followed to ensure both compliance with the OSHA Control of Hazardous Energy Standard and the safety of our employees.

A. Preparation for Lockout or Tagout

Employees who are required to utilize the lockout/tagout procedure must be knowledgeable of the different energy sources and the proper sequence of shutting off or disconnecting energy means. The four types of energy sources are:

- 1. electrical (most common form);
- 2. hydraulic or pneumatic;
- 3. fluids and gases; and
- 4. mechanical (including gravity).

More than one energy source may be utilized on some equipment and the proper procedure must be followed in order to identify energy sources and lockout/tagout accordingly. See Attachment F for specific procedure format.

B. Electrical

- 1. Shut off power at machine and disconnect.
- 2. Disconnecting means must be locked or tagged.
- 3. Press start button to see that correct systems are locked out.
- 4. All controls must be returned to their safest position.
- 5. Points to remember:
 - a. If a machine or piece of equipment contains capacitors, they must be drained of stored energy.
 - b. Possible disconnecting means include the power cord, power panels (look for primary and secondary voltage), breakers, the operator's station, motor circuit, relays, limit switches, and electrical interlocks.
 - c. Some equipment may have a motor isolating shut-off and a control isolating shut-off.
 - d. If the electrical energy is disconnected by simply unplugging the power cord, the cord must be kept under the control of the authorized employee or the plug end of the cord must be locked out or tagged out.

C. Hydraulic/Pneumatic

- Shut off all energy sources (pumps and compressors). If the pumps and compressors supply energy
 to more than one piece of equipment, lockout or tagout the valve supplying energy to the piece of
 equipment being serviced.
- 2. Stored pressure from hydraulic/pneumatic lines shall be drained/bled when release of stored energy could cause injury to employees.
- 3. Make sure controls are returned to their safest position (off, stop, standby, inch, jog, etc.).

D. Fluids and Gases

- 1. Identify the type of fluid or gas and the necessary personal protective equipment.
- 2. Close valves to prevent flow, and lockout/tagout.
- 3. Determine the isolating device, then close and lockout/tagout.
- 4. Drain and bleed lines to zero energy state.
- 5. Some systems may have electrically controlled valves. If so, they must be shut off and locked/tagged out.
- 6. Check for zero energy state at the equipment.

E. Mechanical Energy

Mechanical energy includes gravity activation, energy stored in springs, etc.

- 1. Block out or use die ram safety chain.
- 2. Lockout or tagout safety device.
- 3. Shut off, lockout or tagout electrical system.
- 4. Check for zero energy state.
- 5. Return controls to safest position.

F. Release from Lockout/Tagout

- 1. Inspection: Make certain the work is completed and inventory the tools and equipment that were used.
- 2. Clean-up: Remove all towels, rags, work-aids, etc.

- 3. Replace guards: Replace all guards possible. Sometimes a particular guard may have to be left off until the start sequence is over due to possible adjustments. However, all other guards should be put back into place.
- 4. Check controls: All controls should be in their safest position.
- 5. The work area shall be checked to ensure that all employees have been safely positioned or removed and notified that the lockout/tagout devices are being removed.
- 6. Remove locks/tags. Remove only your lock or tag.

G. Service or Maintenance Involving More than One Person

When servicing and/or maintenance is performed by more than one person, each authorized employee shall place his own lock or tag on the energy isolating source. This shall be done by utilizing a multiple lock scissors clamp if the equipment is capable of being locked out. If the equipment cannot be locked out, then each authorized employee must place his tag on the equipment.

H. Removal of an Authorized Employee's Lockout/Tagout by Berryessa Union School District

Each location must follow the written emergency procedures that comply with 1910.147(e)(3) to be utilized at that location. Emergency procedures for removing lockout/tagout should include the following:

- 1. Verification by employer that the authorized employee who applied the device is not in the facility.
- 2. Make reasonable efforts to advise the employee that his/her device has been removed. (This can be done when he/she returns to the facility).
- 3. Ensure that the authorized employee has this knowledge before he/she resumes work at the facility.

I. Shift or Personnel Changes

Each facility must follow the written procedures based on specific needs and capabilities. Each procedure must specify how the continuity of lockout or tagout protection will be ensured at all times. See 1910.147(f)(4).

J. Procedures for Outside Personnel/Contractors

Outside personnel/contractors shall be advised that Berryessa Union School District has and enforces the use of lockout/tagout procedures. They will be informed of the use of locks and tags and notified about the prohibition of attempts to restart or re-energize machines or equipment that are locked out or tagged out.

The Berryessa Union School District will obtain information from the outside personnel/contractor about their lockout/tagout procedures and advise affected employees of this information.

The outside personnel/contractor will be required to sign a certification form. If outside personnel/contractor has previously signed a certification that is on file, additional signed certification is not necessary.

K. Training and Communication

Each authorized employee who will be utilizing the lockout/tagout procedure will be trained in the recognition of applicable hazardous energy sources, type and magnitude of energy available in the work place, and the methods and means necessary for energy isolation and control.

Each affected employee (all employees other than authorized employees utilizing the lockout/tagout procedure) shall be instructed in the purpose and use of the lockout/tagout procedure, and the prohibition of attempts to restart or re-energize machines or equipment that are locked out or tagged out.

Training will be certified by a training acknowledgement form stating the employee attended and understood the material presented. The certifications will be retained in the employee personnel files.

L. Periodic Inspection

A periodic inspection (at least annually) will be conducted of each authorized employee under the lockout/tagout procedure. This inspection shall be performed by Dan Norris, Director of MOT. If Dan Norris, Director of MOT is also using the energy control procedure being inspected, then another party shall perform the inspection.

The inspection will include a review between the inspector and each authorized employee of that employee's responsibilities under the energy control (lockout/tagout) procedure. The inspection will also consist of a physical inspection of the authorized employee while performing work under the procedures.

Dan Norris, Director of MOT shall certify in writing that the inspection has been performed. The written certification shall be retained in the individual's personnel file.

ATTACHMENT A

List of Authorized Personnel for Lockout/Tagout Procedures

<u>NAME</u>		JOB TITLE
		
·		
	•	

ATTACHMENT B

Lock Out – Tag Out Annual Training

Certification of Training

I certify that I received training as an authorized employer under Berryessa Union School
District Lockout/Tagout program. I further certify that I understand the procedures and wi
abide by those procedures.
AUTHORIZED EMPLOYEE SIGNATURE DATE

ATTACHMENT C

Certification of Training (Affected Personnel)

I certify that I received training as an Affected Employee under the Berryessa Union
School District Lockout/Tagout Program. I further certify and understand that I am
prohibited from attempting to restart or re-energize machines or equipment that are locked
out or tagged out.

AUTHORIZED EMPLOYEE SIGNATURE	DATE

ATTACHMENT D

Lockout/Tagout Inspection Certification

I certify that	(equipment) was inspected on this	date utilizing
lockout/tagout pro	ocedures. The inspection was performed while v	working on
	(equipment).	
	AUTHORIZED EMPLOYEE SIGNATURE	DATE
	INSPECTOR SIGNATURE	DATE

ATTACHMENT E

Outside Personnel/Contractor Certification

I certify that	and	(outside
personnel/contrac	ctor) have informed each other of our respecti	ve lockout/tagout
procedures.		
	AUTHORIZED EMPLOYEE SIGNATURE	DATE
	INSPECTOR SIGNATURE	DATE

ATTACHMENT F

Equipment Specific Procedure for Berryessa Union School District

<u>Machine Identification</u>
General Description:
Manufacturer:
Model Number:
Serial Number:*
* If more than one piece of same equipment, list all serial numbers.
Location of equipment:
Operator Controls
The types of controls available to the operator need to be determined. This should help identify
energy sources and lockout capacity for the equipment.
List types of operator controls:

Energy Sources

The energy sources, such as electrical, steam, hydraulic, pneumatic, natural gas, stored energy, etc.) present on this equipment are:

Lockable

ENERGY SOURCE	LOCATION	Yes	kable No	Type lock or block needed	
ENERGY SOURCE	LOCATION	res	NO	Type lock of block needed	
nutdown Procedures Ist the steps in order necessary secific about how the energy w	to shut down and de-energiz	e the equi I.	pment. E	Be specific. For stored energy	y, be
rocedure:					
ock Type & Location:					

NOTIFY ALL AFFECTED EMPLOYEES WHEN THIS PROCEDURE IS IN APPLICATION.

How Will De-energized State Be Verified?

Start Up Procedures List the steps in order no	ecessary to reactiva	te (energize) the equipm	ent. Be specific.	
Procedure:				
Energy Source Activate	ed:			
NOTIFY ALL AFFECT	ED EMPLOYEES W	HEN THIS PROCEDURI	E IS IN APPLICATION.	
Procedures For Opera	ations and Service/	<u>Maintenance</u>		
	protection must be		29 CFR 1910.147 (a)(2)]. Alterations. Job Safety Analysis is	
Operation Name:				

Affected and Authorized Employees

List each person affected by this procedure and those authorized to use this procedure.

AFFECTED EMPLOYEES			
Name Job Title			
	AUTHORIZED EN	MPLOYEES	
Name Job Title		Job Title	
Approved by		Date	
Approved by		Date	

Updated on 2/2018 and approved through BUSD Safety Committee on 3/2018 Updated on 9/2020

Updated September 2021